

12-TS02

ULTRA-HIGH TACK TISSUE TAPE

PRODUCT DESCRIPTION

High performance synthetic rubber adhesive exhibits exceptional tack and peel strength. The high coat-weight on both sides enables it to key into textured surfaces.

PRODUCT FEATURES

Very high initial tack
 Excellent bond to LSE surfaces
 Soft adhesive flows well into fibrous substrates
 Excellent bond properties to low density foams
 Excellent bond properties to porous substrates

CARRIER

Low Density Tissue

ADHESIVE TYPE

Synthetic Rubber

TOTAL THICKNESS

0.160mm

ADHESIVE TAPE COLOUR

Hazy

RELEASE LINER

Blue/Green Supercalendered Glassine Paper 90gsm

PEEL ADHESION

Medium

SHEAR STRENGTH

Medium High

ELONGATION

2%

CONTINUOUS TEMP. RANGE

-30°C to 60°C

MINIMUM APPLICATION TEMP.

10°C

AVAILABLE WIDTHS

3mm - 1000mm

AVAILABLE FORMATS

Logs, rolls, sheets, discs, pads, and die-cut shapes

SHELF LIFE




1 Year stored at 21°C, 50% RH and out of direct sunlight

MAIN APPLICATIONS (NOT LIMITED TOO)

Bonding thin plastic films, fabrics and other flexible substrates. Used extensively for sail-making and other seam reinforcement applications.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



Berrington House, Berrington Road, Leamington Spa, Warwickshire CV31 1NB		+44 (0) 1926 337466
		sales@tecmanuk.com
		http://www.tecmanuk.com

08
07
06
05
04
03
02
01