

13-FL15

PRODUCT DESCRIPTION

PRODUCT FEATURES

CARRIER

ADHESIVE TYPE

TOTAL THICKNESS

ADHESIVE TAPE COLOUR

RELEASE LINER

PEEL ADHESION

SHEAR STRENGTH

ELONGATION

CONTINUOUS TEMP. RANGE

MINIMUM APPLICATION TEMP.

AVAILABLE FORMATS

SHELF LIFE

MAIN APPLICATIONS (NOT LIMITED TO)

TECHNICAL DATA SHEET

DS PVC/ACRYLIC ADHESIVE FILM TAPE

A white double sided self adhesive tape consisting of a conformable PVC film carrier with a heavy coating of modified acrylic adhesive. Excellent bond on critical materials such as PP, PE & rough surfaces.

Excellent combination of high initial tack & long-term adhesion
Good temperature & UV resistance,
Suitable for outdoor use
Excellent chemical resistance
Available in 3mm- 1250mm widths.

PVC

Modified Acrylic

0.23mm

White

Amber Glassine Paper 65gsm

Very High

High

200%

-35°C to 80°C

15°C

Logs, rolls, sheets, discs, pads, and die-cut shapes

1 Year stored at 21°C, 50% RH and out of direct sunlight

Banner hems, mounting rigid plastics, most metals, wood, rubber & foam, heavy decorative materials & displays, signs & graphics, stair nosing and moulded plastic caps.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC110 | Issue 4 | Sept 2018

Berrington House,
Berrington Road,
Leamington Spa,
Warwickshire
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01