

15-VHPB09

PRODUCT DESCRIPTION

PRODUCT FEATURES

CARRIER

DENSITY

ADHESIVE TYPE

TOTAL THICKNESS

ADHESIVE TAPE COLOUR

RELEASE LINER

PEEL ADHESION

SHEAR STRENGTH

ELONGATION

CONTINUOUS TEMP. RANGE

MINIMUM APPLICATION TEMP.

SHELF LIFE

MAIN APPLICATIONS (NOT LIMITED TO)

TECHNICAL DATA SHEET

VHPB TAPE - 1.14MM WHITE

15-Vhpb09 is a white foamed acrylic tape with very high bond strength to most surfaces. Its specially formulated adhesive makes it one of the most useful Vhpb tapes.

High adhesion to a wide variety of substrates
Good resistance to solvents and moisture
Excellent ageing, UV weathering properties
Resistance to abrasion, corrosion and moisture
Suitable for indoor and outdoor environments
Available in 3mm- 500mm widths
Available as logs, rolls, sheets, discs, pads, and die-cut shapes.

Foamed Acrylic

760 kgm³

Vhpb Acrylic

0.64mm - 2.04mm

White

Printed Glassine Paper 120gsm

Very High

Very High

300%

-40°C to 80°C

15°C

1 Year stored at 21°C, 50% RH and out of direct sunlight

Signage manufacturing, Georgian Bars, Sign channel, Automotive trim and badge attachment, metal and plastic fabrication.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC137 | Issue 5 | Sept 2018

Berrington House,
Berrington Road,
Leamington Spa,
Warwickshire
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01