

15-VHPB TC064

THERMALLY CONDUCTIVE VHPB TAPE

PRODUCT DESCRIPTION

0.64mm thermally conductive acrylic foam tape which provides superior heat transfer for LED units and electronic components. Part of the very high-performance bond range.

PRODUCT FEATURES

Thermally conductive acrylic foam tape. Designed to offer superior transfer of heat from component to heat sinks. Conformable foamed acrylic carrier for improved surface contact. Available in other thicknesses up to 1.2mm.

Main applications include:
 Bonding & mounting components & LED light strips to heat-sinks. Bonding heat generating components to heat sinks or other cooling devices.
 Replacement of thermal grease & mechanical fixtures. Chip on board assemblies, LED/PDP Modules, LED. Signage, backlit TV units, components within desktop, laptop & hand held devices.

CARRIER

Foamed Acrylic Tape

ADHESIVE TAPE COLOUR

White

DENSITY

1500 kgm³

ADHESIVE TYPE

Thermally Conductive Vhpb

TOTAL THICKNESS [ASTM D-1000]

0.64mm

RELEASE LINER

White Paper

PEEL ADHESION

Very High

SHEAR STRENGTH

Very High

SURFACE RESISTANCE [ASTM D-2571]

5.0 x 10¹⁴ Ω




THERMAL CONDUCTIVITY

1 W/(m.K)

VOLUME RESISTANCE [ASTM D-2571]

2.0 x 10¹³ Ω/cm

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request

Berrington House, Berrington Road, Leamington Spa, Warwickshire CV31 1NB		+44 (0) 1926 337466
		sales@tecmanuk.com
		http://www.tecmanuk.com






08
07
06
05
04
03
02
01

08
07
06
05
04
03
02
01

DIELECTRIC BREAKDOWN VOLTAGE [IEC-60243-1]	9.6 kV
DIELECTRIC STRENGTH [IEC-60243-1]	15 kV/mm
SHORT TERM (4HR, 100G) [ASTM D-3654]	160°C
LONG TERM (10,000MIN, 250G) [ASTM D-3654]	100°C
MINIMUM APPLICATION TEMP.	15°C
AVAILABLE WIDTHS	3mm - 400m
AVAILABLE FORMATS	Logs, rolls, sheets, discs, pads, and die-cut shapes
SHELF LIFE	1 year stored at 21 °C, 50 % RH and out of direct sunlight

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request

Berrington House, Berrington Road, Leamington Spa, Warwickshire CV31 1NB		+44 (0) 1926 337466
		sales@tecmanuk.com
		http://www.tecmanuk.com

