

14-FM07

PRODUCT DESCRIPTION

PRODUCT FEATURES

CARRIER

DENSITY

ADHESIVE TYPE

TOTAL THICKNESS

ADHESIVE TAPE COLOUR

RELEASE LINER

PEEL ADHESION

SHEAR STRENGTH

ELONGATION

CONTINUOUS TEMP. RANGE

MINIMUM APPLICATION TEMP.

SHELF LIFE

MAIN APPLICATIONS (NOT LIMITED TO)

TECHNICAL DATA SHEET

LOW TEMPERATURE APPLICATION FOAM TAPE

14-FM07 is a high grade PE foam tape with the latest generation of all Weather acrylic adhesive. This adhesive has been designed to be applied in temperatures as low as -12°C making it an essential product for exterior bonding.

Very good initial bond
Bonds at -12°C
High density PE foam
Good shear strength
Suitable for outdoor use
Available in 3mm- 1600mm widths
Available as logs, rolls, sheets, discs, pads, and die-cut shapes.

High Density Polyethylene

76 Kg/m³

All Weather Acrylic

0.8mm

White

White Glassine Paper 90gsm

High – Foam Destruction

Very High – Substrate Failure

295%

-35°C to 100°C

-12°C

1 Year stored at 21°C, 50% RH and out of direct sunlight

External bonding in extreme conditions. Signage on Oil Rigs, Pipe marking, external aircraft components, Deep sea exploration, IP rated seals, Automotive components.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC115 | Issue 5 | Sept 2018

Berrington House,
Berrington Road,
Leamington Spa,
Warwickshire
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01