

14-FM04

HIGH GRADE EXTERIOR FOAM TAPE

PRODUCT DESCRIPTION

14-FM04 is a high density PE foam tape with high tack modified acrylic adhesive. This tape has been formulated into one of the best performing foam tapes available today.

PRODUCT FEATURES

Very good initial bond
 Excellent bond to foamex, metal and composites
 High density PE foam
 Suitable for external use
 Available in 3mm- 1000mm widths
 Available as logs, rolls, sheets, discs, pads, and die-cut shapes.

CARRIER

High Density PE Foam

DENSITY

98 Kg/m³

ADHESIVE TYPE

Modified Acrylic

TOTAL THICKNESS

0.8mm

ADHESIVE TAPE COLOUR

Black or White

RELEASE LINER

White Glassine Paper 90gsm

PEEL ADHESION (N/25MM)

High – Foam Destruction

SHEAR STRENGTH

Very High

ELONGATION

295%

CONTINUOUS TEMP. RANGE

-35°C to 80°C

MINIMUM APPLICATION TEMP.

15°C

SHELF LIFE




1 Year stored at 21°C, 50% RH and out of direct sunlight

MAIN APPLICATIONS (NOT LIMITED TO)

Sign mounting and fabrication, kickboards, nameplates, glazing bars, decals, badges, Point of Sale, mirror mounting, trunking, decorative moulding, door frame trim and decorative rail.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



Berrington House, Berrington Road, Leamington Spa, Warwickshire CV31 1NB		+44 (0) 1926 337466
		sales@tecmanuk.com
		http://www.tecmanuk.com

08
07
06
05
04
03
02
01