

PRODUCT DATA SHEET

0250540

PRODUCT DESCRIPTION

PRODUCT FEATURES

PROTECTION FILM - AUTOMOTIVE SERIES

0250540v0 is a surface protection film designed for painted and unpainted plastic components suitable for long-term outdoor exposure.

A premium grade self-adhesive film developed for the protection of delicate surfaces, such as painted bumpers.

- Conformable polyolefin carrier film
- Suitable for a wide range of exterior paint finishes
- Tested at speeds over 160 km/h 100mph
- Available with dispensing equipment
- Environmentally friendly film and adhesive
- Common uses include:
 - Protection of piano black paint systems
 - Protection of PMMA and ASA moulded parts
 - Protection of exterior panels

BACKING MATERIAL Polyolefinic Film

TOTAL THICKNESS 75 µm

ADHESIVE TYPE Synthetic Rubber

ADHESION TO STEEL 1.5 N/cm

ADHESIVE TAPE COLOUR White

ELONGATION AT BREAK 450%

TENSILE STRENGTH 16 N/cm

UV RESISTANCE 24 weeks

EASY TO REMOVE Yes

SUITABLE FOR DIE-CUTTING Yes

PAINT COMPATIBILITY Very Good

RESISTANCE TO CHEMICALS Very Good

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a convict partial bloom product. copy is available on request

Berrington House, Berrington Road, Leamington Spa, Warwickshire

CV31 1NB

+44 (0) 1926 337466



sales@tecmanuk.com



http://www.tecmanuk.com

