

**0230960**

**PROTECTION FILM - AUTOMOTIVE SERIES**

**PRODUCT DESCRIPTION**

High adhesion edge securing tape for freshly painted surfaces.

07

**PRODUCT FEATURES**

Ensures high strength adhesion and can be used to keep protection films securely in place, especially in areas of difficult geometries to prevent dust and humidity penetration.

Protection film consists of an UV-stabilised backing coated with a high adhesion EVA adhesive.

- Paint protection during outdoor storage up to 12 months
- Secure adhesion during transport
- Easy disposal - both the film and the adhesive system are environmentally friendly

06

**BACKING MATERIAL**

Polyolefinic Film

**TOTAL THICKNESS**

96 µm

**ADHESIVE TYPE**

EVA

**ADHESION TO STEEL**

3 N/cm

**ADHESIVE TAPE COLOUR**

White

**ELONGATION AT BREAK**

660%

**TENSILE STRENGTH**

21.5 N/cm

**UV RESISTANCE**

52 weeks

**EASY TO REMOVE**

Yes

**SUITABLE FOR DIE-CUTTING**

Yes

**PAINT COMPATIBILITY**

Very Good

**RESISTANCE TO CHEMICALS**

Very Good

**MAIN APPLICATION (NOT LIMITED TOO)**

Die-cutting and as printed marking, security or steering labels. Base material for heavy duty protection pads for bumpers and door edges.

04

03

02

01

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC087 | Issue 4 | Mar 2019

Berrington House,  
Berrington Road,  
Leamington Spa,  
Warwickshire  
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>