

1110501

PRODUCT DESCRIPTION

PRODUCT FEATURES

TECHNICAL DATA SHEET

LOW TACK PROTECTION FILM

Low tack PE surface protection film

Also available in clear or green Low tack clean peel adhesive Suitable for printed media (Subject to trial)

CARRIER

ADHESIVE TYPE

TOTAL THICKNESS

ADHESIVE TAPE COLOUR

PEEL ADHESION (180° PEEL)

ELONGATION

CONTINUOUS TEMP. RANGE

MINIMUM APPLICATION TEMP.

AVAILABLE WIDTHS

AVAILABLE FORMATS

PΕ

Acrylic

0.05mm

Blue

Very Low

180%

60°C

15°C

50mm - 1250mm

Rolls

MAIN APPLICATIONS (NOT LIMITED TOO)

Protection of glass, printed media, uPVC, Screens, LCD displays smooth plastic sheets, varnished surfaces, acrylicand synthetic resin varnish, high-grade steel, polished brass.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request

Berrington House, Berrington Road, Leamington Spa, Warwickshire CV31 1NB



+44 [0] 1926 337466



sales@tecmanuk.com



http://www.tecmanuk.com

