

1310501

LOW TACK PROTECTION FILM

08

07

06

05

04

03

02

01

PRODUCT DESCRIPTION

Low tack PE surface protection film

PRODUCT FEATURES

Also available in blue or green
 Low tack clean peel adhesive
 Suitable for printed media (Subject to trial)

CARRIER

PE

ADHESIVE TYPE

Acrylic

TOTAL THICKNESS

0.05mm

ADHESIVE TAPE COLOUR

Clear

PEEL ADHESION (180° PEEL)

Very Low

ELONGATION

180%

CONTINUOUS TEMP. RANGE

60°C

MINIMUM APPLICATION TEMP.

15°C

AVAILABLE WIDTHS

50mm – 1250mm




AVAILABLE FORMATS

Rolls

MAIN APPLICATIONS (NOT LIMITED TOO)

Protection of glass, printed media, uPVC, Screens, LCD displays smooth plastic sheets, varnished surfaces, acrylic- and synthetic resin varnish, high-grade steel, polished brass.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request

Berrington House, Berrington Road, Leamington Spa, Warwickshire CV31 1NB		+44 (0) 1926 337466
		sales@tecmanuk.com
		http://www.tecmanuk.com

