

15-VHPB10

VHPB TAPE – 0.64MM GREY

08
07
06
05
04
03
02
01

PRODUCT DESCRIPTION

15-Vhpb10 is part of our Signmakers Range of Vhpb tapes. These exceptional products offer true Vhpb performance at economical pricing.

PRODUCT FEATURES

Good initial bond
 Resistant to moisture, plasticiser and Ultra violet {UV} light
 Resistant to abrasion, corrosion
 Bonds medium and high surface energy substrates
 Alternative to 3M™ RP32
 Available in 3mm - 800mm widths
 Available in logs, rolls, sheets, discs, pads, and die-cut shapes

CARRIER

Foamed Acrylic

DENSITY

780 kgm³

ADHESIVE TYPE

Acrylic Foam

TOTAL THICKNESS

0.64mm

ADHESIVE TAPE COLOUR

Grey

RELEASE LINER

Red Siliconised Film 0.085mm

PEEL ADHESION

Very High

SHEAR STRENGTH

Very High

ELONGATION

300%

CONTINUOUS TEMP. RANGE

-40°C to 100°C

MINIMUM APPLICATION TEMP.

0°C




SHELF LIFE

1 Year stored at 21°C, 50% RH and out of direct sunlight

MAIN APPLICATIONS (NOT LIMITED TO)

Signage manufacturing, metals and composites, sign channel to aluminium and PVC, glazing bars, Automotive Trim attachment, Constructional bonding and exterior mounting.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request. 3M™ is a trademark of 3M™.

Berrington House, Berrington Road, Leamington Spa, Warwickshire CV31 1NB		+44 (0) 1926 337466
		sales@tecmanuk.com
		http://www.tecmanuk.com

