

## 15-VHPB11

### PRODUCT DESCRIPTION

### PRODUCT FEATURES

#### CARRIER

#### DENSITY

#### ADHESIVE TYPE

#### TOTAL THICKNESS

#### ADHESIVE TAPE COLOUR

#### RELEASE LINER

#### PEEL ADHESION

#### SHEAR STRENGTH

#### ELONGATION

#### CONTINUOUS TEMP. RANGE

#### MINIMUM APPLICATION TEMP.

#### SHELF LIFE

#### MAIN APPLICATIONS (NOT LIMITED TO)

# TECHNICAL DATA SHEET

## VHPB TAPE – 1.14MM GREY

15-Vhpb11 is part of our Signmakers Range of Vhpb tapes. These exceptional products offer true Vhpb performance at economical pricing.

Good initial bond  
Resistant to moisture, plasticiser and Ultra violet (UV) light  
Resistant to abrasion, corrosion  
Bonds medium and high surface energy substrates  
Alternative to 3M™ RP45  
Available in 3mm - 800mm widths  
Available in logs, rolls, sheets, discs, pads, and die-cut shapes

Foamed Acrylic

780 kgm<sup>3</sup>

Acrylic Foam

1.14mm

Grey

Red Siliconised Film 0.085mm

Very High

Very High

300%

-40°C to 100°C

0°C

1 Year stored at 21°C, 50% RH and out of direct sunlight

Signage manufacturing, metals and composites, sign channel to aluminium and PVC, glazing bars.  
Constructional bonding and exterior mounting.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request. 3M™ is a trademark of 3M™.



REGISTERED IN ENGLAND: 9216154

DOC139 | Issue 7 | Jan 2023

Berrington House,  
Berrington Road,  
Leamington Spa,  
Warwickshire  
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01