

11-TR11

PRODUCT DESCRIPTION

PRODUCT FEATURES

ADHESIVE TYPE

TOTAL THICKNESS

ADHESIVE TAPE COLOUR

RELEASE LINER

PEEL ADHESION

SHEAR STRENGTH

CONTINUOUS TEMP. RANGE

MINIMUM APPLICATION TEMP.

AVAILABLE WIDTHS

AVAILABLE FORMATS

SHELF LIFE

MAIN APPLICATIONS (NOT LIMITED TO)

TECHNICAL DATA SHEET

CONDUCTIVE TRANSFER ADHESIVE TAPE

A modified acrylic transfer adhesive loaded with electrically conductive particles. The product is electrically conductive through the Z axis.

Very high bond strength
Conforms to UL723
Resistivity of 0.005 ohm. Volume resistivity of 0.5 ohms-cm
Suitable for external use

Conductive Acrylic

0.051mm

Hazy

White MS Kraft Paper 120gsm

Medium High

Medium High

-34°C to 107°C

15°C

3mm - 1250mm

Logs, rolls, sheets, discs, pads, and die-cut shapes

1 Year stored at 21°C, 50% RH and out of direct sunlight

Anti-static components, conductive gaskets, Earth strips, replacing solder points.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC125 | Issue 5 | Apr 2023

Berrington House,
Berrington Road,
Leamington Spa,
Warwickshire
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01