

15-VHPB03

PRODUCT DESCRIPTION

PRODUCT FEATURES

CARRIER

DENSITY

ADHESIVE TYPE

TOTAL THICKNESS

ADHESIVE TAPE COLOUR

RELEASE LINER

PEEL ADHESION

SHEAR STRENGTH

ELONGATION

CONTINUOUS TEMP. RANGE

MINIMUM APPLICATION TEMP.

SHELF LIFE

MAIN APPLICATIONS (NOT LIMITED TOO)

TECHNICAL DATA SHEET

VHPB TAPE - 1.0MM CLEAR

A glass clear foamed acrylic tape with very high bond strength to most high surface energy surfaces. Its solid construction and clear characteristics make it one of the most useful Vhpb tapes.

Glass clear
Excellent bond to acrylics
Suitable for outdoor use
Bonds most metals and finishes
Available in 3mm- 800mm widths
Available as logs, rolls, sheets, discs, pads, and die-cut shapes.

Foamed Acrylic Vhpb Tape

850 kgm³

Vhpb Acrylic

1.0mm

Glass Clear

Red Siliconised Film 0.085mm

Very High

Very High

900%

-30°C to 100°C

-15°C

1 Year stored at 21°C, 50% RH and out of direct sunlight

Sign channel, glass, rigid plastics, foamed PVC, aluminium composite, acrylic fabrication, metal fabrication, trim attachment, light box fabrication, badge mount, GRP fabrication, sign fabrication.

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC132 | Issue 8 | May 2024

Berrington House,
Berrington Road,
Leamington Spa,
Warwickshire
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01