

15-VHPB AG110

PRODUCT DESCRIPTION

PRODUCT FEATURES

CARRIER

DENSITY

ADHESIVE TYPE

TOTAL THICKNESS

ADHESIVE TAPE COLOUR

RELEASE LINER

180 PEEL ADHESION (ASTM D-3330)

SHEAR STRENGTH (ASTM D1002)

ELONGATION AT BREAK

UV RESISTANCE

CONTINUOUS TEMP. RANGE

SHORT TERM TEMP. RESISTANCE

MINIMUM APPLICATION TEMP.

TECHNICAL DATA SHEET

1.14MM GREY AUTOMOTIVE GRADE

1.14mm grey automotive grade Vhpb tape which provides excellent adhesion to automotive plastics and painted steel.

Developed for the automotive industry and has excellent adhesion to automotive plastics and painted steel.

UL 746C approval on metals, plastics and glass.

Applications Include:
Automotive plastics and painted steel
Sign industry applications
Construction industry applications
Automotive aftercare market

Available widths: 3mm - 800mm

Foamed Acrylic

781 kgm³

Vhpb Acrylic

1.14mm

Grey

Red Siliconised Film 0.085mm

3900 gf/25mm

6000 cgf/cm²

900%

Very Good

-40°C to 100°C

-40°C to 160°C

15°C

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request



REGISTERED IN ENGLAND: 9216154

DOC173 | Issue 2 | May 2024

Berrington House,
Berrington Road,
Leamington Spa,
Warwickshire
CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



<http://www.tecmanuk.com>

08

07

06

05

04

03

02

01