

14-FM11

PRODUCT DESCRIPTION

PRODUCT FEATURES

TECHNICAL DATA SHEET

POLYETHYLENE FOAM TAPE

14-FM11 is a double sided closed cell polyethylene foam tape with high quality acrylic cross-linked adhesive.

Delivers excellent all round bonding performance in the most demanding applications.

Excellent all round bonding performance in the most demanding applications

Double sided closed cell polyethylene foam

High quality acrylic cross-linked adhesive

Very good UV resistance

CARRIER Closed Cell Polyethylene Foam

DENSITY 100 Kg/m³

ADHESIVE TYPE Acrylic

FOAM THICKNESS 800 µm

ADHESIVE TAPE COLOUR Black

RELEASE LINER White (also available in blue & green)

180° PEEL ADHESION 820 N/m

DYNAMIC SHEAR 75 N/cm²

TEMP. RESISTANCE -30°C to 90°C

MAIN APPLICATIONS (NOT LIMITED TO)

Permanent bonding, mounting and fixing applications.

SHELF LIFE: 1 YEAR STORED AT 23°C, < 85% RH AND OUT OF DIRECT SUNLIGHT

The information given is believed to be reliable and typical, but should only be used as a guide. The buyer shall satisfy himself prior to ordering that the product is suitable for the purpose for which the buyer requires it. Should the product subsequently prove to be unsuitable Tecman Speciality Materials Ltd shall not be held liable for any consequential damage or loss incurred. All goods are sold in accordance with our standard trading Terms and Conditions, of which a copy is available on request

Berrington House, Berrington Road, Leamington Spa, Warwickshire CV31 1NB



+44 (0) 1926 337466



sales@tecmanuk.com



http://www.tecmanuk.com

